UTILITY
PATENT APPLICATION
TRANSMITTAL
(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 35.C14864

First Named Inventor or Application Identifie

SHUMPEI TAKENAKA ET AL.

	PTO	
	.S.	
er	с. 68ј	
	98	
	Ĵα	

늗	<u> </u>						Express Mail Eaber No.			
	APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents			ts	Commissioner for Patents ADDRESS TO: Box Patent Application Washington, DC 20231					
	1. X	Fee Transm (Submit an ori	nittal Form iginal, and a duplic	ate for fee pro	ocessing)		7.	CD-ROM or Program (A		e, large table or Computer
	2.	Applicant claims small entity status. See 37 CFR 1.27.				8.	Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)			
	3. X	Specification Total Pages 18					a. Computer Readable Form (CRF)			
	4. X Drawing(s) (35 USC 113) Total Sheets 9					b. Specification Sequence Listing on: i CD-ROM or CD-R (2 copies); or				
	5.	Oath or Declaration Total Pages					ii. paper			
		a. N	ewly executed (original or copy)			c. Statements verifying identity of above copies ACCOMPANYING APPLICATION PARTS				
3		h C	ony from a prior	application	(37 CED 4 62(d))			ACCOM	PANTING APPLI	CATION PARTS
		b. Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 6 below])	9.		Papers (cover sheet	& document(s))	
State Street Str		i. DELETION OF INVENTOR(S) Signed Statement attached deleting inventor(s) named in the prior application, see 37 CFR 1 63(d)(2) and 1 33(b)							(b) Statement e is an assignee)	Power of Attorney
						` ' [nslation Document (if applicable)	,
i l	6. X	Application Data Sheet. See 37 CFR 1.76			}	12.	Statement (IDS)/PTO-1449 Citation			
	13 Preliminary Amendment									
							14. X	Return Rec	eipt Postcard (MP specifically itemiz	PEP 503) ed)
							15. Certified Copy of Priority Document(s) (if foreign priority is claimed) 16. Other:			
						}				
-	17 If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:									
	Continuation Divisional Continuation-in-part (CIP) of prior application No/									
1	Prior application information: Examiner Group/Art Unit:									
- } <	For CONTINUATION OR DIVISIONAL APPS only. The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be									
-	relied upon when a portion has been inadvertently omitted from the submitted application parts									
• -	18 CORRESPONDENCE ADDRESS 05514									
	X Customer Number or Bar Code Label (Insert Customer No. or Attach bar code label here) or Correspondence address below						spondence address below			
	NAME									
\[Address									
	City		<u> </u>	1	State	1		 1	Zip Code	
-	Country				Telephone				Fax	

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS		
	TOTAL CLAIMS (37 CFR 1 16(c))	14-20 =	0	X \$ 18.00 =	\$0		
	INDEPENDENT CLAIMS (37 CFR 1.16(b))	8-3 =	5	X \$ 80.00 =	\$400.00		
	MULTIPLE DEPENDENT	\$270.00 =	\$0				
		\$710.00					
		\$1110.00					
	Reduction by	0					
	TOTAL = \$1110.00						
19. Sn	nall entity status						
19. Sn a. b. c.	A small er A small er and desire	ntity statement is enclose ntity statement was filed in ed. er claimed.		al application and suc	h status is still proper		
a. b. c.	A small er A small er and desire Is no long	ntity statement was filed in ed.	n the prior nonprovision		h status is still proper		
a. b. c.	A small er A small er and desire Is no long X A check in the amo	ntity statement was filed in ed. er claimed.	n the prior nonprovision	nclosed.	h status is still proper		
a. b. c. 20.	A small er A small er and desire Is no long X A check in the amo	ntity statement was filed in ed. er claimed. ount of \$_1110.00 to ount of \$ to c	n the prior nonprovisions cover the filing fee is er over the recordal fee is	nclosed. enclosed.			
a. b. c. 20.	A small er A small er and desire Is no long X A check in the amo A check in the amo Commissioner is hereby 0.06-1205:	ntity statement was filed in ed. er claimed. ount of \$_1110.00 to ount of \$ to c	n the prior nonprovisions cover the filing fee is er over the recordal fee is	nclosed. enclosed.			
a. b. c. 20 21 22. Th	A small er A small er and desire Is no long X A check in the amount A check in the amount Commissioner is hereby Commissioner is hereby A check in the amount E Commissioner is hereby E Commissioner is hereby E Commissioner is hereby	ntity statement was filed in ed. er claimed. bunt of \$_1110.00 to bunt of \$ to compare to compare the compare to compare the compare to compare the comp	n the prior nonprovisions cover the filing fee is er over the recordal fee is	nclosed. enclosed.			

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED				
NAME	Jack M. Arnold			
SIGNATURE	Jock M. arnold Peg. No. 25,823			
DATE	October 10, 2000			

Form #125

INVENTOR INFORMATION

Inventor One Given Name:: SHUMPEI

Family Name:: TAKENAKA

Postal Address Line One:: 2-19, Tsukimino 4-chome,

City:: Yamato-shi

State or Province:: Kanagawa-ken,

Country:: Japan

Inventor Two Given Name:: YUKINOBU

Family Name:: SUWA

Postal Address Line One:: 20-23-804, Mitsuzawa Shimo-machi,

Postal Address Line Two:: Kanagawa-ku

City:: Yokohama-shi,

State or Province:: Kanagawa-ken

Country:: Japan

CORRESPONDENCE INFORMATION

Correspondence Customer Number:: 05514

Fax:: (212) 218-2200

APPLICATION INFORMATION

Title Line One:: IMAGE PROCESSING APPARATUS AND METHOD

Title Line Two:: THEREFOR

Total Drawing Sheets:: 9
Formal Drawings?:: Yes
Application Type:: Utility
Docket Number:: 35.C14864

Secrecy Order in Parent Appl.?:: No

REPRESENTATIVE INFORMATION

Representative Customer Number:: 5514

PRIOR FOREIGN APPLICATIONS

Foreign Application One:: 11-289375

Filing Date:: 12, October, 1999

Country:: Japan

Priority Claimed:: Yes

10

15

20

25

IMAGE PROCESSING APPARATUS AND METHOD THEREFOR

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an image processing apparatus for efficiently arranging and printing, on a designated sheet, all the image data or selected ones thereof, obtained by a device such as a digital camera or the like and stored in a memory medium, and an image processing method and a memory medium adapted for use therefor.

Related Background Art

In case of printing plural images on a printing sheet by designating division therein in a conventional printing apparatus, the number of printed images, the printing positions and the printing areas are defined as invariable values, so that the sheet and the images to be printed are designated in the unit of each sheet.

Also in such conventional printing apparatus, in case of printing plural desired images on a printing sheet, the images are printed as a size according to the sheet size, so that the magnification of the images varies according to the sheet size and it is not possible to print the desired image with the desired size on the sheet.

10

15

20

25

SUMMARY OF THE INVENTION

In consideration of the foregoing, the image processing apparatus of the present invention is characterized by designation means for designating the size of the image to be printed on the sheet, and process means for executing a process of printing the image designated by the designation means.

The image processing apparatus of the present invention is also characterized by designation means for designating the image size to be printed on the sheet and means for executing a layout process for the sheet with the image size designated by the designation means.

The image processing apparatus of the present invention is also characterized by designation means for designating the sizes of the images to be printed on a page, means for designating the number of images, and process means for editing and printing, on a page, with a layout based on the images according to the designation by the designation means.

The image processing apparatus of the present invention is also characterized by designation means for designating the images to be printed and the partition of the images for changing the page, and process means adapted, in printing the images designated by the designation means, to execute a page changing process upon detection of the partition of the

20

images designated by the designation means.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of a control apparatus

for an electronic image;

Fig. 2 is a flow chart showing an example of printing control;

Fig. 3 is a flow chart showing an example of printing control with priority on the number of images;

10 Fig. 4 is a flow chart showing printing control in case the image size and the number of images are both designated;

Fig. 5 is a flow chart for a condition setting 1;

Fig. 6 is a flow chart for a condition setting 2;

Fig. 7 is a flow chart for a condition setting 3;

Fig. 8 is a flow chart for a condition setting 4;

Figs. 9A and 9B are respectively a block diagram and an external view of a digital camera;

Fig. 10 is a flow chart for condition setting with the digital camera; and

Figs. 11A, 11B and 11C are views showing example of images printed on a sheet.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Now the present invention will be explained by embodiments thereof, with reference to the accompanying drawings.

Fig. 1 is a block diagram of a control apparatus for an electronic image. As an external memory device 2, a non-volatile memory medium can be chosen as an example. An external memory device 2 is detachably mountable on a digital camera and also on the present control apparatus, and stores the image data taken for example by the digital camera as an image file. The above-mentioned non-volatile memory medium may also contain a print object designation/condition file for defining the print object image and the print condition such as the printing sheet. Also instead of employing the detachable memory medium, the control apparatus in the present invention may incorporate a memory device for storing a file transferred directly from the digital camera or through a memory medium.

The image designation for arranging images on a sheet is executed from an input part 6. Such image designation includes the setting of various conditions for example of designation of a sheet size such as B4, A4, B5 or A5, that of a print sheet size such as a whole sheet, a half sheet, a quarter sheet or a sixth sheet of the newspaper size, number of image divisions per printing sheet or image size (represented by sheet size or by image dimension), the designation of an appropriate layout mode. When the image signal is selected and designated, the number thereof is from time to time stored in an image printing object

register area 8A in a memory 8, and the number of an image counter area 8B in the memory 8 is at the same time increased by one and is newly stored in a total image number register 8C therein. Then, as a condition for arranging and printing plural images on a page, a partition number for designating the number of divisions or the number of images to be arranged on a page is entered manually from the input part 6 and is stored in a partition number register 8D of the memory 8. Similarly the desired number of sheets is stored in a page number register 8E in the memory 8, and the desired print sheet size is stored in a page size register 8F. Also the desired image size is stored in an output image size register 8G.

A partition number register 8D in the memory 8 stores a number of additional images and a condition of layout permissible in case of maintaining the printed image size, determined from the sheet and the partition number, and the minimum distance of the images, by referring to a partition table based on the maximum partition layout condition and the partition number at the completion of sheet setting. A decode/distribution process distributes and stores, in case an external memory device 2 (for example a non-volatile memory medium storing image data) contains an image to be printed and a condition designating file corresponding to the image, the results of decoding of such content

10

15

20

25

CPU.

in the total image number register 8C, the image printing object register 8A, the partition number register 8D, the page number register 8E, the page size register 8F and the output image size register 8G. image decode/decompression process executes decoding of the compressing condition of data compressed for example by JPEG and decompression of the data. information 18 obtained by the image decode/decompression part 3 is supplied to a central processing unit (CPU) 1, and the layout condition is determined from the print output size and the output resolution, by referring to the areas in the memory 8, namely the total image number register 8C, the image printing object register 8A, the partition number register 8D, the page number register 8E, the sheet size register 8F and the output image size register 8G. A printing device 5 converts the image data, decompressed according to the result of the CPU 1, into print data matching the printing apparatus and transfers such print data thereto. For calculating the layout condition, the CPU 1 acquires and stores in advance various conditions relating to the print layout such as the printable area, through a print control Programs corresponding to the flow charts shown in Figs. 2 to 8 are stored in a read-only memory (ROM) of a memory 7 shown in Fig. 1, and are executed by the

The programs stored in the ROM may be stored in

10

15

20

25

another memory medium or may be loaded from an external memory into an internal memory.

In the embodiment of the present invention, in a printing apparatus provided with means for entering image number information etc. for specifying the image data stored in the non-volatile memory medium, a control part for decoding and decompressing the image data, a control part for printing the image data and decoding means for the non-volatile memory medium storing the print object and condition designating file prepared in advance by image designating means outside the present apparatus for example that of a digital camera, the print object image information obtained by an input of the print object image number or by decoding the print object and condition designating file is stored in a specified memory part of the apparatus, and the images designated by thus stored information are arranged in succession on the printing sheet according to the image layout condition of the designated sheet whereby the printing with automatic page change is continued until all the images are printed.

At first reference is made to Fig. 5 for explaining a first condition setting process for designating an image.

At first, in a step S11, an image to be designated is entered manually from the input part 6. Then a step

10

20

25

S12 stores the total number of the designated images in the total image number register 8C. Than a step S13 stores the image number of the image designated by the input part 6 in the image printing object register 8C.

Then reference is made to Fig. 6 for explaining a second condition setting process for designating the sheet size.

At first, in a step S21, an input on the sheet to be designated is entered from the input part 6. Then a step S22 stores the sheet size entered from the input part 6 in the sheet size register 8F.

Then reference is made to Fig. 7 for explaining a third condition setting process for designating the partition number.

At first, in a step S31, a partition number is manually entered from the input part 6. Then a step S32 stores the partition number, entered from the input part 6, in the partition number register 8D.

Then reference is made to Fig. 8 for explaining a fourth condition setting process for designating an image size.

At first, in a step S41, an image size is entered from the input part 6. Then a step S42 stores the image size entered from the input part 6 in the image size register 8G.

In the following there will be explained, with reference to Fig. 2, a process in case the printing is

10

15

20

25

instructed by the user after the aforementioned first to fourth condition settings. Each condition setting is achieved either automatically or by entering a numerical condition. The automatically set condition becomes lower in priority in case another condition is entered by the numerical value.

In the following there will be explained a case where the image is to be outputted with a desired size on the sheet or the number of images to be outputted on the sheet is designated while the image size is automatically set.

At first, in step S1801, it is checked whether a plural images on the output sheet are arranged or not. If "NO" in step S1801, an image read from the file is output to an image layout register for outputting an image with the designated image size on the sheet in step S1812 as shown in Fig. 11B. On the other hand, if "YES" in step S1801, the sequence proceeds to step S1802 for discriminating whether the priority is given to the image size and the number of images is automatically set. If the priority is given to the image size, the sequence proceeds to step S1803 for setting "1" in a register N. Then step S1804 checks whether the images of a number of the register N can be accommodated in the sheet. If affirmative, step S1805 transfers an image Gn from the file into the image layout register, and next step S1806 checks whether a

10

15

20

next image Gn+1 is present. If not, step S1811 sends an image layout storing the images up to the image Gn+1 to the printing apparatus and executes output on the output sheet as shown in Fig. 11A. If affirmative, a process for adding N+1 into N (N = N+1) is executed in step S1807, and it is checked whether the image Gn is added to the image layout on the sheet in step S1808. That is, there is checked, from the sheet size and the image size, whether the plural images can be laid on If the result is negative, the images up to the sheet. Gn+1 stored in the image layout register is output to the printing sheet in step S1809. If the result in the step S1804 is negative, step S1810 executes output to the image layout register by reducing the output size on the sheet, and then to the printing apparatus for printing as shown in Fig. 11C. Then there is executed a process N = N+1 on the register N, and the sequence returns to step S1804.

In case step S1802 identifies that the priority is given to the image size and the number of images is not automatically set, the sequence proceeds to the flow chart shown in Fig. 3, wherein step S1901 discriminates whether the priority is given to the number of images and the image size is automatically set.

If affirmative, step S1902 checks the sheet size, then stores the designated number of images in the image layout register of the memory 8 according to a

10

15

20

25

template, and then the images are printed on the output sheet (S1903). Then there is searched, in the memory medium of the external memory device, whether a next image is present (S1904). If present, the sequence returns to step S1902, but, if not, the sequence is terminated.

If the result of step S1901 is negative, the sequence proceeds to the flow chart shown in Fig. 4.

In step S2001, it is checked whether the image size and the number of images are both designated. Ιf the both designations are absent, the sequence is terminated, but, if they are present, the sequence proceeds to step S2002 for discriminating whether the designated output is possible on the sheet. designated output is possible, there are executed the output of a sheet (step S2007) and a page change process for proceeding to a next sheet (step S1008). On the other hand, if the designated output is not possible, an image is arranged with priority on the image size in step S2003. Then step S2004 discriminates whether at least an image can be placed. If possible, there is executed output (step S2005), but, if not, there is executed output with a reduction in the size (step S2009). Then step S2006 checks whether a next image is present. If absent, the sequence is terminated, but, if present, the sequence returns to step S2001 for repeating the above-described procedure.

5

10

15

20

25

Fig. 9A is a block diagram of a digital camera 100 shown in Fig. 9B, wherein an input part 101 is used for designating the setting of mode etc. A processing part 102 includes a CPU 1021, a ROM 1022, and a RAM 1023. The ROM 1022 stores the procedure shown in Fig. 10. The RAM 1023 stores an image fetched by the input means in correlation with the image size designated by the designation means for designating the image size. The RAM 1023 corresponds to the memory 8 shown in Fig. 1. An image is taken from an input part 101 or an image pickup part, and the image and the attribute information defined therefor are stored through an external memory device 104. Such external memory device 2 shown in Fig. 1.

At first the taken image is displayed on a display device 103. Then, according to a program of the ROM 7, there are entered, from the input part 101, the size of the image to be outputted and the instruction for example for executing or not the printing. Fig. 10 shows the process flow to be executed by the CPU for defining the image size (large (L), medium (M) or small (S)) for the image. The display device 103 displays the image, and, in such display state, the image size for such image is entered from the input part (steps S2101, S2111, S2121). The image and the image size

10

15

20

data are stored in an external memory device 104 (steps S2101, S2112, S2122).

In the foregoing embodiment, the image control apparatus for executing the image control can be a digital camera, a computer or an image printing order receiving processing device (i.e. printer).

Also an image processing software may be utilized within each device.

The present invention allows to obtain the print result desired by the user with the designation of the image size, in contrast to the conventional method in which the image designation and the printing operation have to be repeated in the unit of each page.

Consequently it is rendered possible to executing the printing without size designation at the printing operation, and, as the output size can also be designated on the displayed image instead of on the printing, the image can be reproduced with the desired size on the display, so that the image can be rendered visible in the desired size, in a simpler manner than in the conventional technology.

WHAT IS CLAIMED IS:

 An image processing apparatus comprising: designation means for designating the image size of an image to be printed on a sheet; and

process means for executing a page change process for each layout of the image size designated by said designation means.

- An image processing apparatus according to
 claim 1, further comprising printing means for printing an image.
 - 3. An image processing apparatus comprising: designation means for designating the size of images to be printed on a page;

designation means for designating the number of images to be printed on a page; and

process means for executing a process of printing images on a page according to the designation by either of said designation means.

- 4. An image processing apparatus according to claim 3, further comprising printing means for printing said images.
 - 5. An image processing method comprising:
 a step of designating the image size of an image

25

15

20

to be printed on a sheet; and

a process step of executing a page change process for each layout of the image size designated by said designation step.

5

An image processing method according to claim
 further comprising a printing step of printing an image.

10

7. A memory medium comprising:

a step of storing the image size of an image to be printed on a sheet, designated by designation means; and

a process step of executing a page change process

for each layout of the image size designated by said
storing step.

8. A memory medium comprising:

a memory step of storing the image size of images

to be printed on a page, designated by designation

means;

a memory step of storing the number of images to be printed on a page, designated by designation means; and

a process step of executing a process of layout of images on a page based on the image size or the number of images stored in either of the foregoing steps.

- 9. An image processing apparatus comprising: image fetching means for fetching an image; designation means for designating the size of the image to be printed on a sheet; and
- memory control means for storing, in mutual correlation, the image fetched by said image fetching means and the image size designated by said designation means.
- 10. An image processing apparatus according to claim 9, wherein said image fetching means includes image pickup means for taking an image.
- 11. An image processing apparatus according to

 15 claim 10, wherein said image fetching means is adapted
 to fetch the image taken by said image pickup means
 through a memory medium.
- 12. An image processing apparatus according to claim 11, wherein said memory medium is detachable.
 - 13. An image processing apparatus comprising: designation means for designating the image size of the image to be outputted; and
- process means for executing a page change process for each layout with the image size designated by said designation means.

- 14. An image processing apparatus comprising:

 means for receiving images with designated image
 sizes, to be printed on a sheet; and
- means for executing layout of the said images and

 outputting said images, with the mutual correlation of
 the image fetched by said receiving means and the
 designated image size.


ABSTRACT OF THE DISCLOSURE


In conventional printing apparatus, in case of printing plural desired images on a printing sheet, the images are printed as a size according to the sheet size, so that the magnification of the images varies according to the sheet size and it is not possible to printing the desired image with the desired size on the sheet.

In order to solve the foregoing problem, it is

provided, an apparatus for designating the size of an image to be printed on a sheet, arranging images on a sheet.










FIG. 4







FIG. 5 THE FIRST CONDITION SETTING 15S11 **DESIGNATE IMAGES** S12 STORE THE TOTAL NUMBER OF IMAGES INTO THE REGISTER FOR TOTAL NUMBER OF IMAGES S13 STORE THE IMAGE NUMBER INTO IMAGE PRINTING OBJECT REGISTER **END**












FIG. 9B




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C

